

# GENERAL SEALANTS, INC.

## GS# A-800-3G Sealant

### Technical Data Sheet

#### PRODUCT DESCRIPTION

GS# A-800-3G Sealant is an ultra-high temperature vacuum bag sealant tape formulated from a blend of silicones, used primarily for high temperature thermoplastic processing. It is the highest temperature rated vacuum bag sealant available and is structurally reinforced with flame retardant, heat stabilizing fibers, and adheres well to high-temperature Thermalimide film. The product gets tackier when heated. GS# A-800-3G Sealant is ideal for autoclave cure cycles from 350°F (177°C) to 800°F (427°C).

#### PRODUCT ADVANTAGES

- Can intermittently withstand temperatures of 800°F (426°C)
- Strips clean from tooling surface post cure
- No special tools required
- Fast and easy to apply by hand
- Non-Hazardous
- Adheres to Thermalimide film
- Autoclave cures from 350°F (177°C) to 800°F (427°C)

#### APPLICATION

Surface should be clean and dry for maximum bond. Apply the sealant by hand to the tooling surface pressing the sealant firmly into place. When ready to apply the film, remove the release liner from the sealant and apply the film to the sealant. It is recommended to use a roller to run the entire area of the sealant applying firm pressure to achieve the best seal.

Product is not considered hazardous to skin however wash hands before eating. DO NOT TAKE INTERNALLY.



#### TYPICAL PHYSICAL PROPERTIES

<b>Chemical Base</b>	Silicone
<b>Color</b>	Light Green
<b>Specific Gravity (ASTM D 792)</b>	1.01
<b>Total Solids</b>	100%
<b>Penetration (ASTM D 217) cone at 72°F / 150 grams</b>	62-75 (6.2 to 7.5 mm)
<b>Rolling Ball Tack (ASTM D 3121)</b>	< 25.0 cm (11/16" Ball)
<b>Elongation (ASTM D 1000)</b>	> 300%
<b>Weight Loss (ASTM C 771)</b>	< 3.0%
<b>Odor</b>	None
<b>Adhesion</b>	Good
<b>Water Resistance</b>	Excellent
<b>Corrosion Resistance</b>	Good
<b>Service Temperature</b>	Room temp. to 800°F (427°C)
<b>Shelf Life (Storage At 72°F/22°C)</b>	12 Months from DOM

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.

## GS# A-800-3G Sealant

### Technical Data Sheet

#### PACKAGING

GS# A-800-3G Sealant is available in a wide range of extruded sizes supplied in roll form on a release liner. The standard sizes are 1/8" x 1/2" x 25' (40 Rolls/Case) and 1/8" x 3/4" x 25' (28 Rolls/Case) but other custom sizes are available.

#### STORAGE AND HANDLING

Material should be stored at 72°F (22°C) in a dry area in its original sealed case and case must remain right side up.

For more information on GS# A-800-3G Sealant, please email [Sales@GeneralSealants.com](mailto:Sales@GeneralSealants.com) or call (800)-762-1144 to speak with our Sales Department.

#### USER'S RESPONSIBILITY

THIS PRODUCT INFORMATION CANNOT COVER ALL POSSIBLE SITUATIONS, WHICH THE USER MAY EXPERIENCE DURING PROCESSING. EACH ASPECT OF YOUR OPERATION SHOULD BE EXAMINED TO DETERMINE IF, OR WHERE, ADDITIONAL PRECAUTIONS MAY BE NECESSARY. ALL HEALTH AND SAFETY INFORMATION CONTAINED IN THIS BULLETIN SHOULD BE PROVIDED TO YOUR EMPLOYEES OR CUSTOMERS. IT IS YOUR RESPONSIBILITY TO USE THIS INFORMATION TO DEVELOP APPROPRIATE WORK PRACTICE GUIDELINES AND EMPLOYEE INSTRUCTIONAL PROGRAMS FOR YOUR OPERATION.

#### DISCLAIMER OF LIABILITY

AS THE CONDITIONS OR METHODS OF USE ARE BEYOND OUR CONTROL, WE DO NOT ASSUME ANY RESPONSIBILITY AND EXPRESSLY DISCLAIM ANY LIABILITY FOR ANY USE OF THIS MATERIAL. INFORMATION CONTAINED HEREIN IS BELIEVED TO BE TRUE AND ACCURATE BUT ALL STATEMENTS OR SUGGESTIONS ARE MADE WITHOUT WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THE INFORMATION, THE HAZARDS CONNECTED WITH THE USE OF THE MATERIAL OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS REMAINS THE RESPONSIBILITY OF THE USER.

#### CONFIDENTIALITY NOTICE

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION BELONGING TO THE SENDER, WHICH IS LEGALLY PRIVILEGED. THE INFORMATION IS INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY NAMED ABOVE. IF YOU ARE NOT THE INTENDED RECIPIENT, BE AWARE THAT ANY DISCLOSURE, COPYING, DISTRIBUTION OR USE OF THIS INFORMATION IS PROHIBITED. IF YOU HAVE RECEIVED THIS IN ERROR, PLEASE CONTACT US IMMEDIATELY AND DELETE (DESTROY) THE DOCUMENT.

#### WARRANTY

PRODUCTS ARE SOLD WITHOUT WARRANTY, EXPRESSED OR IMPLIED, EXCEPT IF SHOWN TO BE DEFECTIVE IN MATERIALS WITHIN 30 DAYS OF SHIPMENT BY GENERAL SEALANTS, IT WILL BE REPLACED OR AT GENERAL SEALANTS OPTION THE PURCHASE PRICE WILL BE REFUNDED TO THE PURCHASER. GENERAL SEALANTS ASSUMES NO RESPONSIBILITY FOR CONSEQUENTIAL DAMAGE ARISING FROM THE USE OF OUR PRODUCTS. USER MUST CONFIRM THE ADAPTABILITY OF OUR PRODUCTS BY THEIR OWN TEST. NO REPRESENTATIVE OF GENERAL SEALANTS OR ANY OTHER COMPANY HAS AUTHORIZATION TO GRANT ANY ADDITIONAL WARRANTY.